



Horn speaker, professional 2 way, waterproof for long range outdoor amplification.
Ideal for stadiums, sports halls, squares..

EN60849 EN54-24 certificated certification nr 0068/CPR/170-2022.

UV resistant

Impedance: 100V / 80hm

Nominal power 100V: 200W/100/50/25 W. 400 peak

Power 8 Ohm: 250W RMS. 1000W peak

Sensitivity (PN 1W/1mt): 96 dB - SPL max @200W: 118 dB

Max output level / full power 129dB (100V)

Max output level / full power 130dB (8 Ohm)

Dispersion 60° (V/H) 1KHz

Dispersion 45° (V/H) 5KHz

Frequency response: 80-18000 Hz +/-10dB

Size with bracket (WxHxD): 360x296x392mm

Size without bracket (WxHxD): 360x296x345mm

Weight 13,5 Kg

Colour RAL7035

Suitable for screw fixing

ABS Cabinet white painted. Painted stainless steel protection grille.


Vivaldi srl ongoing effort to improve its products, reserves the right to make technical and aesthetic changes effectively without

VIVALDI

obligation to notice

 Images

Vivaldi EN54 PH210TPRO



Vivaldi srl

Via E. Fermi, 8 Z.I. EST - 30020 Noventa di Piave (Venezia) ITALIA
Tel. +39 0421 307825 - info@vivaldigroup.it - www.vivaldigroup.it
P.IVA e C.F. 02880360272