



Professional FULL RANGE active, 2-way loudspeaker.
Bi-amplified Class D amplification.
With DSP processor: 5 different selectable presets.
For vertical or horizontal use.
15" woofer with 3" voice coil, high power.
Titanium driver 1.4" with 2" voice coil, high power.
RMS Power: 1500W.
Max Power: 3000W.
Useful Range (-10dB): 42Hz~20KHz.
Max SPL: 126dB / 138dB(Peak).
Mic Input: COMBO XLR/Jack (2-way).
Line Input: COMBO XLR/Jack, RCA.
Line Output: XLR.
Power Supply: AC100V - AC240V.
Dimensions 420x726x465 mm (WxHxD).
Stand tube diameter 35mm (D).
Weight 31Kg.
2 handles.
Plywood cabinet.
Scratch-proof painted finish.
Stand tube diameter 35 mm (vertical use).

VIVALDI

Black colour.

Vivaldi srl ongoing effort to improve its products, reserves the right to make technical and aesthetic changes effectively without obligation to notice

 Images

Vivaldi PRO SP15A



Vivaldi srl

Via E. Fermi, 8 Z.I. EST - 30020 Noventa di Piave (Venezia) ITALIA
Tel. +39 0421 307825 - info@vivaldigroup.it - www.vivaldigroup.it
P.IVA e C.F. 02880360272