



Communication Gateway for EVAC systems and ModBus RTU protocol.
Modbus address configuration via DipSwitch
Status LED for Modbus and LINK communication
Audible alarm in case of failed communication or EVAC LINK connection

TECHNICAL INFO:

- Size (WxHxD): 36x90x63 mm (2 DIN rail modules)
- Power supply: 12-24 Vdc (via [Vivaldi Giove AL2B](#), supplied)
- Certifications: RoHS, CE

PROTOCOLS MANAGED:

- EVAC (RJ45 LINK)
- ModBus RTU (Supervision)

CONNECTIONS:

- 1x RS485 (ModBus RTU)
- 1x RJ45 (EVAC LINK)
- 1x 12-24 VDC power supply

KIT INCLUDES:

- EVO.BRIDGE

VIVALDI

- User manual
- Power supply [Vivaldi Giove AL2B](#)

Vivaldi srl ongoing effort to improve its products, reserves the right to make technical and aesthetic changes effectively without obligation to notice

Images

Vivaldi EN54 EVO.BRIDGE



Vivaldi srl

Via E. Fermi, 8 Z.I. EST - 30020 Noventa di Piave (Venezia) ITALIA
Tel. +39 0421 307825 - info@vivaldigroup.it - www.vivaldigroup.it
P.IVA e C.F. 02880360272