



Rectangular speaker, 2-way built-in, **HI-FI, IP31**.

EN60849 EN54-24 certified. Certification number 0068-CPR-059/2017 when install:

-Built-in with it's box [Vivaldi Ulisse SR10](#)

-In-Wall installation with fire resistant cover [Vivaldi EN54 SR10ENX](#).

Loudspeaker: woofer 11 cm.

Tweeter 1,3 cm mylar.

Nominal power 1,5/3/6W RMS. 12W, max 99dB

Transformer voltage 100V.

Frequency response 70-20000 Hz.

Sensitivity: 87 dB. max 1 mt 94 dB.

Speaker dimensions (WxHxD) 147x222x65 mm.

In-built hole (WxH) 120x195 mm.

Weight 1,1 Kg.

Cabinet ABS V0 with painted galvanized grille.

Colour: black RAL9011

Installation in-wall: fire resistant and anti humidity built case [Vivaldi Ulisse SR10](#).

Fire resistant and anti humidity cover for overhanging wall or ceiling installation [Vivaldi EN54 SR10ENX](#)

Installation on plasterboard, wood walls or similar: no accessories needed, the speaker is provided in the rear with hook-shaped anchors for stable fixing.

VIVALDI

Vivaldi srl ongoing effort to improve its products, reserves the right to make technical and aesthetic changes effectively without obligation to notice

 Images

Vivaldi EN54 GIADA10TB



Vivaldi srl

Via E. Fermi, 8 Z.I. EST - 30020 Noventa di Piave (Venezia) ITALIA
Tel. +39 0421 307825 - info@vivaldigroup.it - www.vivaldigroup.it
P.IVA e C.F. 02880360272