



Professional sound projector, HiFi, 2 way, IP65, EN60849, EN54-24 certified.

Supplied with bracket for wall mounting, 3 positions (-30°, 0°, +30°). Up and over 180°O/180°V.

Woofer 10,5 cm

Dome Tweeter 2,5 cm, Polyamide

Dispersion angle 105°Vx90°O (120° up to 3 KHz)

Nominal power 100V: 5/10/20W. 40W peak, max 105dB.

Power 8 Ω: 30W RMS, 60W musical

Suggested amplification from 10 to 50W RMS

Impedance 8 Ω - 100V selectable

Frequency range 75-20000 Hz -10dB

Sensitivity 85 dB

Max output level / full power 102 dB.

Dimensions (WxHxD) without bracket 170x250x147 mm

Dimensions (WxHxD) with bracket 170x243x180 mm

Weight 2,4 Kg

Cabinet ABS V0, painted aluminum bracket and grille.

Available colours: black RAL9005 ([Vivaldi EN54 FLORA10TB](#)) - white RAL9003 ([Vivaldi EN54 FLORA10TW](#))

Working temperature from -20° to +80°.

VIVALDI

Vivaldi srl ongoing effort to improve its products, reserves the right to make technical and aesthetic changes effectively without obligation to notice

 Images

Vivaldi EN54 FLORA10T



Vivaldi srl

Via E. Fermi, 8 Z.I. EST - 30020 Noventa di Piave (Venezia) ITALIA
Tel. +39 0421 307825 - info@vivaldigroup.it - www.vivaldigroup.it
P.IVA e C.F. 02880360272

VIVALDI



Vivaldi srl

Via E. Fermi, 8 Z.I. EST - 30020 Noventa di Piave (Venezia) ITALIA
Tel. +39 0421 307825 - info@vivaldigroup.it - www.vivaldigroup.it
P.IVA e C.F. 02880360272