



Professional sound projector, in **Hi-Fi** version, 3-way, with subwoofer.

IP66 protection. Ideal for outdoor applications even in marine areas. Resistant to corrosive agents such as chlorine and salt.

Supplied with bracket for wall mounting.

Convex elliptical passive subwoofer 10.5x15 cm (WxH).

Woofer 13 cm in polypropylene, graphite finish.

Tweeter 2.5 cm domed, in neodymium and silk.

Dispersion angle 105°Vx90°H (120° up to 3 KHz).

Rated power at 100V: 2,5/5/10/20W. 40W peak, max 104dB.

8 Ω power: 60W RMS, 120W music.

Recommended amplification from 10 to 80W RMS.

Impedance 8 Ω - 100V selectable.

Frequency response 55-20000 Hz.

Sensitivity 85 dB.

Max output level / full power 105 dB.

Size (WxHxD) without bracket 170x258x168 mm.

Size (WxHxD) with bracket 170x258x185 mm.

Weight 2,76 Kg.

ABS cabinet, bracket and grille in painted aluminum.

Available colors white RAL 9003 with edges RAL7035 ([Vivaldi Ulisse ANNA13TW](#)) and black RAL9005 ([Vivaldi Ulisse ANNA13TB](#)).

VIVALDI

Working temperature from -20° to +80°.

Vivaldi srl ongoing effort to improve its products, reserves the right to make technical and aesthetic changes effectively without obligation to notice

 Images

Vivaldi Ulisse ANNA13T



Vivaldi srl

Via E. Fermi, 8 Z.I. EST - 30020 Noventa di Piave (Venezia) ITALIA
Tel. +39 0421 307825 - info@vivaldigroup.it - www.vivaldigroup.it
P.IVA e C.F. 02880360272