



Professional sound projector, in **Hi-Fi** version, 3-way, with subwoofer.

IP66 protection. Ideal for outdoor applications even in marine areas. Resistant to corrosive agents such as chlorine and salt.

Supplied with bracket for wall mounting.

Convex elliptical passive subwoofer 16.5x23.5 cm (WxH).

Woofer 20.5 cm in polypropylene, graphite finish.

Tweeter 2.8 cm domed, in neodymium and silk.

Dispersion angle 105°Vx90°H (120° up to 3 KHz).

Rated power at 100V: 6,25/12,5/25/50W. 100W peak, max 108dB.

8 Ω power: 80W RMS, 160W music.

Recommended amplification from 10 to 100W RMS.

Impedance 8 Ω - 100V selectable.

Frequency response 45-20000 Hz.

Sensitivity 87 dB.

Max output level / full power 106.5 dB.

Size (WxHxD) without bracket 250x381x250mm.

Size (WxHxD) with bracket 250x381x280 mm.

Weight 5,01 Kg.

ABS cabinet, bracket and grille in painted aluminum.

White color RAL9003 with RAL7035 edges.

Working temperature from -20° to +80°.

VIVALDI

Vivaldi srl ongoing effort to improve its products, reserves the right to make technical and aesthetic changes effectively without obligation to notice

 Images

Vivaldi Ulisse ANNA20TW



Vivaldi srl

Via E. Fermi, 8 Z.I. EST - 30020 Noventa di Piave (Venezia) ITALIA
Tel. +39 0421 307825 - info@vivaldigroup.it - www.vivaldigroup.it
P.IVA e C.F. 02880360272