



Speaker, 2-way coax, **Hi-Fi**, IP65\* waterproof.

Woofer: 20.5 cm.

Tweeter: 2.5 cm.

**Nominal power at 100V: 15/30/60W RMS. 120 peak, max. 108dB.**

**Nominal power at 70V: 15/30/60W RMS.120 peak.**

**8Ω power: 80W RMS, 160W musical.**

Recommended amplification: 10 to 100W RMS

**Impedance: 70V/100V - 8Ω selectable**

Frequency response 55-20000 Hz.

Sensitivity: 90dB. Max 108dB 1W/1mt.

Dimensions (DxH) 380x450 mm.

Weight 3.8Kg.

Colour bronze brown - RAL8014.

Cabinet: UV polypropylene.

Degree of protection: IP65.

Angle of dispersion: 360°(H)x40°(V).

Working temperature: -20° to +60°.

*Vivaldi srl ongoing effort to improve its products, reserves the right to make technical and aesthetic changes effectively without obligation to notice*

# VIVALDI



Images

**Vivaldi Ulisse**  
**EARTHSOUND.BRZ**



**Vivaldi** srl

Via E. Fermi, 8 Z.I. EST - 30020 Noventa di Piave (Venezia) ITALIA  
Tel. +39 0421 307825 - info@vivaldigroup.it - www.vivaldigroup.it  
P.IVA e C.F. 02880360272