



HiFi version sound projector, 2 way, **HiFi, IP32**

EN60849, EN54-24 certificate. Certification number 0068-CPR-017/2016

Supplied with bracket for wall mounting.

Woofer 10 cm

Tweeter 2,5 cm

Mylar diaphragm.

Dispersion angle 90°Vx90°O (120° fino a 3 KHz).

Nominal power to 100V: 1,25/2,5/5/10W. 20W peak, max 104dB

Power 8 Ω: 30W RMS, 60W musical.

Suggested amplification from 10 to 30W RMS

Impedance 8 Ω - 100V selectable.

Frequency response 80-20000 Hz -10dB

Sensitivity 91 dB

Max output level / full power 101 dB.

Dimensions (WxHxD) without bracket 151x215x130 mm.

Dimensioni (WxHxD) with bracket 151x245x163 mm.

Weight 1,9 Kg.

VIVALDI

Cabinet ABS V0, with galvanized and painted steel bracket and grill

Black colour

Working temperature from -20° to $+80^{\circ}$

Vivaldi srl ongoing effort to improve its products, reserves the right to make technical and aesthetic changes effectively without obligation to notice

 Images

Vivaldi EN54 LARA9TB



Vivaldi srl

Via E. Fermi, 8 Z.I. EST - 30020 Noventa di Piave (Venezia) ITALIA
Tel. +39 0421 307825 - info@vivaldigroup.it - www.vivaldigroup.it

P.IVA e C.F. 02880360272