



**IP 65** waterproof horn speaker, **certified EN60849 EN54-24 certification nr 0068-CPR-035/2016.**

UV resistant.

**Input: 100V.**

**Nominal power: 1,9/3,8/7,5/15W. Peak 30W.**

**Power to 8 Ohm: 30W RMS.**

Frequency response 250-8000 Hz - 10dB.

Sensitivity 106 dB.

Max output level / full power 117 dB.

Dispersion 110°(V) 90°(H) 2KHz.

Dimensions without bracket: (WxHxD) 220x164x231 mm.

Dimensions with bracket: (WxHxD) 220x181x231 mm.

Weight 1,4 Kg.

Colour RAL9035.

Cabinet: ABS V0, painted stainless steel U bracket.

ABS V0 elliptical shape.

Working temperature from -20° to + 60°.

*Vivaldi srl ongoing effort to improve its products, reserves the right to make technical and aesthetic changes effectively without obligation to notice*

# VIVALDI

 Images

## Vivaldi EN54 PH15MK2



**Vivaldi** srl

Via E. Fermi, 8 Z.I. EST - 30020 Noventa di Piave (Venezia) ITALIA  
Tel. +39 0421 307825 - info@vivaldigroup.it - www.vivaldigroup.it  
P.IVA e C.F. 02880360272