



**IP 65** waterproof horn speaker, 2-way, **HI-FI**, **certified EN60849 EN54-24 certification nr 0068-CPR-035/2016.**

UV resistant.

Woofer 16,5 cm.

Compressure tweeter.

**Input: 100V.**

**Nominal power: 15/30/50W. Peak 100W.**

Frequency response: 100-16000 Hz - 10dB.

Sensitivity 101dB.

Max output level / full power 117 dB.

Dispersion 100°(V) 60°(O) 2KHz.

Dimensions without bracket: (WxHxD) 356x268x294 mm.

Dimensions with bracket: (WxHxD) 356x280-312x294 mm.

Weight 3,9 Kg.

Colour RAL7035.

Cabinet: ABS, painted stainless steel U bracket.

ABS V0 rectangular shape.



Working temperature from -20° to + 60°.

*Vivaldi srl ongoing effort to improve its products, reserves the right to make technical and aesthetic changes effectively without obligation to notice*

# VIVALDI

 Images

## Vivaldi EN54 PH50HIFI



**Vivaldi** srl

Via E. Fermi, 8 Z.I. EST - 30020 Noventa di Piave (Venezia) ITALIA  
Tel. +39 0421 307825 - info@vivaldigroup.it - www.vivaldigroup.it  
P.IVA e C.F. 02880360272