



Professional sound projector, **Hi-Fi**, 2-way, **certified EN60849 EN54-24 certification nr 0068-CPR-035/2016**. IP65 protection. **Ideal for outdoor applications even in marine areas. Resistant to corrosive agents as chlorine and salt.**

Supplied with bracket for wall mounting.

Rotating bracket 90° vertical, 170° horizontal.
Woofer 13,5 cm.
Dome tweeter 2,5 cm, titanium.
Dispersion angle 105°Vx90°O (120° up to 3 KHz).
Nominal power 100V: 2/4/8/16/32W. 64Wpeak.
Power 8 Ω: 60W RMS, 120W musical.
Suggested amplification from 10 to 80W RMS.
Impedance 8 Ω - 100V selectable.
Frequency response 65-20000 Hz.
Sensitivity 87 dB.
Max output level / full power 103 dB.
Dimensions (WxHxD) without bracket 186x257x165 mm.
Dimensions (WxHxD) with bracket 186x257x187 mm.
Weight 2,4 Kg.

VIVALDI

V0 ABS cabinet, bracket and metal grille.
Black colour RAL9005.
Working temperature from -20° to +80°.

Vivaldi srl ongoing effort to improve its products, reserves the right to make technical and aesthetic changes effectively without obligation to notice

 Images

Vivaldi EN54 FLORA13TB



Vivaldi srl

Via E. Fermi, 8 Z.I. EST - 30020 Noventa di Piave (Venezia) ITALIA
Tel. +39 0421 307825 - info@vivaldigroup.it - www.vivaldigroup.it
P.IVA e C.F. 02880360272

VIVALDI



Vivaldi srl

Via E. Fermi, 8 Z.I. EST - 30020 Noventa di Piave (Venezia) ITALIA
Tel. +39 0421 307825 - info@vivaldigroup.it - www.vivaldigroup.it
P.IVA e C.F. 02880360272