



In-ceiling 2-way round speaker with steel flame-resistant cap, Frameless series Flush with the wall.

EN60849, EN54-24 Certified. Certification number 0068-CPR-059/2017.

Steel frame with protection grill

Woofer: 16,5cm (6,5"), polypropylene

Tweeter: 1,9, dome, Mylar, neodymium magnet

Nominal power: 2/4/8/16/32W. 64W peak, max 104dB.

Transformer voltage: 100V

Frequency response: 65-20000 Hz - 10dB.

Sensitivity: 86 dB

Max output level / full power: 101 dB

Speaker dimensions (DxD): 284x155 mm

Recessed installation hole (D): 262mm

Weight: 2,9 Kg

Grille colour: white RAL9016

Cabinet: V0 ABS, V0 metal protection grill

Operation temperature: from -20° to +65°

Installation on plasterboard, wood walls or similar: no accessories needed, the speaker is provided rear hooks for stable anchoring

Installation in-wall (concrete): not suitable

VIVALDI

Vivaldi srl ongoing effort to improve its products, reserves the right to make technical and aesthetic changes effectively without obligation to notice

 Images

Vivaldi EN54 ROUND17TF



Vivaldi srl

Via E. Fermi, 8 Z.I. EST - 30020 Noventa di Piave (Venezia) ITALIA
Tel. +39 0421 307825 - info@vivaldigroup.it - www.vivaldigroup.it
P.IVA e C.F. 02880360272