



Design floorstand speaker, 100% Made In Italy  
in extruded aluminum (4mm thickness) with anti-resonance shapes.  
2-way system.

1 High quality 25 mm treated silk dome tweeter, high power  
neodymium magnet circuit with high performance heat sink.

2 Mid-bass XTDD, 13,5 cm with phase adjustment

Frequency range 70Hz - 22.000Hz.

Sensitivity 92 dB.

**Impedance 4Ω.**

**Power (RMS) 140W.**

**Power (PROGRAM) 280W.**

Suggested amplification power: 30-150W.

Cabinet: 4mm thick extruded aluminum.

Standard finish: matt black.

Fabric coated cover grill

Customizable finishes: cabinet colour and coating,

grille (on demand)

Dimensions: (WxHxD): 160x920x145 mm.

Weight 12 Kg.

Floor stand, wall stand or design bracket on request

# VIVALDI

Optional accessories:

- wall bracket, rotation up to 160° and +/- 10° inclination, [Vivaldi LUX QTower50](#)

IMPORTANT: QTower speakers by default come with no bracket holes.

Please indicate if holes are required when ordering.

-floor stand (project, material and quotation on demand).

\* Ideal for HiFi stereo use or as center, front or rear channel in Home Theatre systems.

*Vivaldi srl ongoing effort to improve its products, reserves the right to make technical and aesthetic changes effectively without obligation to notice*

## Images

## Vivaldi LUX QTower2



**Vivaldi** srl

Via E. Fermi, 8 Z.I. EST - 30020 Noventa di Piave (Venezia) ITALIA  
Tel. +39 0421 307825 - [info@vivaldigroup.it](mailto:info@vivaldigroup.it) - [www.vivaldigroup.it](http://www.vivaldigroup.it)

P.IVA e C.F. 02880360272

# VIVALDI

**Vivaldi** srl

Via E. Fermi, 8 Z.I. EST - 30020 Noventa di Piave (Venezia) ITALIA  
Tel. +39 0421 307825 - [info@vivaldigroup.it](mailto:info@vivaldigroup.it) - [www.vivaldigroup.it](http://www.vivaldigroup.it)  
P.IVA e C.F. 02880360272