



Design column speakers, for professional mid/far-field range applications (conference rooms, theatre, hotels,..), 100% Made in Italy in extruded aluminum with (4 mm thickness) with anti-resonance design.

2-way system.

1 neodymium compression driver tweeter 25mm, high efficiency, horn loaded 80° dispersion angle.

6 Mid-bass XTDD, 13,5 cm with re-phasing configuration.

Frequency range 65Hz - 20.000Hz.

Sensitivity 96 dB.

**Impedance 5,5Ω.**

**Power (RMS) 350W.**

**Power (PROGRAM) 700W.**

Suggested amplification power: 80-350W.

Cabinet: 4mm thick extruded aluminum.

Standard finish: matt black.

Removable cloth grille.

Customisable finishes: cabinet colour and coating, grille (on demand).

Dimensions: (WxHxP): 160x1420x145 mm.

Weight 25 Kg.

Floor stand, wall stand or shelf stand installation

Optional accessories:

- wall bracket, rotation up to 160° and +/- 10° inclination,

# VIVALDI

Vivaldi G&G QTowerSO.

IMPORTANT: QTower speakers by default come with no bracket holes.

Please indicate if holes are required when ordering.

-floor stand (project, material and quotation on demand).

*Vivaldi srl ongoing effort to improve its products, reserves the right to make technical and aesthetic changes effectively without obligation to notice*

 Images

## Vivaldi LUX QTower6PRO



**Vivaldi** srl

Via E. Fermi, 8 Z.I. EST - 30020 Noventa di Piave (Venezia) ITALIA  
Tel. +39 0421 307825 - info@vivaldigroup.it - www.vivaldigroup.it  
P.IVA e C.F. 02880360272