



Design column speaker, for professional mid/far-fiel range applications (conference rooms, theatres, hotels,..), 100% Made in Italy in extruded aluminum (4 mm thickness) with anti-resonance design.

1 neodymium compression driver tweeter 25mm, high efficiency, horn loaded 80° dispersion angle.

8 Mid-bass XTDD, 13,5 cm with re-phasing configuration.

Frequency range 65Hz - 20.000Hz.

Sensitivity 99 dB.

Impedance 8Ω.

Power (RMS) 500W.

Power (PROGRAM) 1000W.

Suggested amplification power: 80-500W.

Standard finish: matt black.

Removable cloth grille.

Customisable finishes: cabinet colour and coating, grille (on demand).

Dimensions: (WxHxD): 160x2020x145 mm.

Weight 30 Kg.

Optional accessories:

- wall bracket, rotation up to 160° and +/- 10° inclination,

Vivaldi G&G QTowerSO.

IMPORTANT: QTower speakers by default come with no bracket holes.

Please indicate if holes are required when ordering.

VIVALDI

-floor stand (project, material and quotation on demand).

Vivaldi srl ongoing effort to improve its products, reserves the right to make technical and aesthetic changes effectively without obligation to notice



Images

Vivaldi LUX QTower8PRO



Vivaldi srl

Via E. Fermi, 8 Z.I. EST - 30020 Noventa di Piave (Venezia) ITALIA
Tel. +39 0421 307825 - info@vivaldigroup.it - www.vivaldigroup.it
P.IVA e C.F. 02880360272