



2-way bi-amplified speaker, Bass-Reflex

Applications: Live Sound P.A., D.J. Systems, Restaurants, Pub, Club, Auditorium, Theatres, Gym..

20 cm (8") woofer, ceramic magnet

25mm (1") Compression driver and 32mm (1,5") coil

LF Amplifier 100W RMS

HF Amplifier 25W RMS

Control panel with Input, MIC, Line, XLR, Link Output

Separate Mic Level and Line Level + Master Volume 2-band tone

control (Bass, Treble)

Clip power LED

90°H x 60°V Horn

Frequency response 70Hz - 18kHz -6dB

Sensibility 95dB

Maximum SPL / peak 116/119 dB

Dispersion 90°x60° (HxV)

Crossover frequency 2.5 KHz

Connectors: IN XLR-JACK-PIN, OUT XLR JACK

Microphone input XL/JACK mixabile

4 M8 holes, 35mm stand hole

Bracket mount for wall installation

1 built-in handle

# VIVALDI

Dimensions: 265x410x240 mm (WxHxD)

Weight 7,3Kg

ABS cabinet

Colour Anthracite grey

Power supply 240V/50-60Hz

*Vivaldi srl ongoing effort to improve its products, reserves the right to make technical and aesthetic changes effectively without obligation to notice*

## Images

## Vivaldi Ulisse SOUND8A



**Vivaldi** srl

Via E. Fermi, 8 Z.I. EST - 30020 Noventa di Piave (Venezia) ITALIA  
Tel. +39 0421 307825 - info@vivaldigroup.it - www.vivaldigroup.it

P.IVA e C.F. 02880360272

# VIVALDI



**Vivaldi** srl

Via E. Fermi, 8 Z.I. EST - 30020 Noventa di Piave (Venezia) ITALIA  
Tel. +39 0421 307825 - [info@vivaldigroup.it](mailto:info@vivaldigroup.it) - [www.vivaldigroup.it](http://www.vivaldigroup.it)  
P.IVA e C.F. 02880360272